

RS Tine Drill





RS400

RS480

RS500

RS600

The new RS Tine Drill represents the most reliable answer when high speed drilling is required in heavy or stony soil. Five rows of high clearance tine coulters ensure trouble free drilling in trashy and wet condition.



STANDARD EQUIPMENT

- 5 rows of straight seeding tines
- Accord metering system
- 2+2 Tramline computer controlled
- 2+2 track eradicators
- 2 rows precision following harrow
- Hopper capacity 1500 l
- 3 steps and platform
- Hydraulic disc markers adjustable for tractor wheel or centre marking
- Four 26x12-12 tyre wheels -2 on 4mt
- Fan PTO drive 1000 RPM
- Set of lights for road transport
- 3mt transport width



OPTIONALS



- Fan Hydraulic Drive
- Hopper Extension
- Pre-Emerg Markers
- DRILLTRONIC MAX with variable seed rate
- Hydraulic Cross Board
- V Harrow Tines with Press Wheels
- Half Width Shut Off
- PTO Shaft



MODEL	RS400	RS480	RS500	RS600
WORKING WIDTH mt	4	4.8	5	6
POWER REQUIREMENT HP	150	170	180	190
TRANSPORT WIDTH mt	3	3	3	3
HOPPER CAPACITY	1500Lt	1500Lt	1500Lt	1500Lt
No. OF COULTERS	32	38	40	48
WEIGHT Kg.	1760	2000	2100	2190

CONCEPT PERUGINI S.p.A.
 MACCHINE AGRICOLE

Via Dell'Artigianato 11 - 47014 MELDOLA - ITALY
 PHONE: +390543494602 - FAX: +390543494727
 Email: sales@conceptagri.com

www.conceptagri.com